# VIBOCOLD®



Oslo series

Item no.: OSC 100S

Convenience cooler with a straight front glass

Ventilated cooling and electronic control



## Dimensions, volume and weight

Net volume	220
External dimensions (WxDxH)	950 x 755 x 1365 mm
Internal dimensions (WxDxH)	894 x 470 x 730 mm
Package dimensions (WxDxH)	1050 x 950 x 1600 mm
Display area	0.95 m²
Gross Weight	225 kg
Net weight	210 kg

## **Technical cooling specifications**

Defrosting	Automatic
Refrigerant, charge	140 g
Refrigerant	R290

#### **Design and materials**

Doors, numbers	2 pcs.
Door, features	Soft-close and self-close
Door	Sliding glass door
Reversible door	No
Exterior	Black / RAL 9005

#### Performance and consumption

Cooling temperature interval	-1 to 5 °C
Climate class	3
Energy consumption (kWh/year)	3103 kWh/year
Energy consumption (kWh/day)	8.5 kWh/day
Noise level	60 dB(A)
Temperatur class	MI
Execution	Ventilated

#### Connection

Input power	800 W
Voltage	230 V
Frequency	50 Hz
Phases	1

#### Equipment

Number of shelfes	3 pcs.
Shelf, type	Glass shelf
Feet and legs	Adjustable screw feet

Interior	Black
Panel type	Glass
Horizontal light, no.	4 pcs.
Horizontal light, type	LED light at the top and under the shelf
Light, effect	44 W
Controller	Electronic
Controller, technical	Carel Easy

# Approvals and standards

EEI indeks	45 %
Energy classification	D